

KEKB Roadmap




K. Oide for the KEKB Accelerator Group

25 March 2008

IHEP, Protovino









Table 1: Machine parameters of KEKB

Date	11/15/2006		Design		
	LER	HER	LER	HER	
Current	1.65	1.33	2.6	1.1	A
Bunches/ring	1389		5000		
Bunch current	1.19	0.96	0.52	0.22	mA
Bunch spacing	1.8-	-2.4		0.6	\mathbf{m}
Emittance ε_x	18	24	18	18	\parallel nm \parallel
$\parallel eta_x^*$	59	56	33	33	cm $ $
$\parallel eta_y^*$	0.65	0.59	1.0	1.0	cm $ $
Hor. size @ IP	103	116	77	77	$\mu \mathrm{m}$
Ver. size @ IP	1.9	1.9	1.9	1.9	$\mu\mathrm{m}$
Beam-beam ξ_x	0.115	0.075	.039	.039	
Beam-beam ξ_y	0.101	0.056	.052	.052	
Bunch length	7	6	4	4	mm
Luminosity	17	.12		10	/ nb/s
∫Lum./day	\sim 12	232	\sim	600	\parallel /pb \parallel
\int Lum./7 days/	7.	82		_	/fb
\int Lum./30 days	30	.21		_	/fb

70% higher than the design

doubled the design


The power of Continuous Injection Mode






Crab cavities will be installed and tested with beam in 2006.


e+ 4.1 A



The superconducting cavities will be upgraded to absorb more higher-order mode power up to 50 kW.



The beam pipes and all vacuum components will be replaced with higher-current-proof design.



will reach 8×10^{35} cm⁻²s⁻¹.

Three factors to determine the luminosity:

Stored current:

 $1.7 / 1.4 A (e^{+}/e^{-}KEKB)$

→ **9.4** /**4.1** A (SuperKEKB)

Beam-beam parameter:

0.059 (KEKB)

→ >0.24 (SuperKEKB)

Lorentz factor

$$L = \frac{\gamma_{\pm}}{2er_e} \left(1 + \frac{\sigma_y^*}{\sigma_x^*} \right) \frac{I_{\pm} \xi_{\pm y}}{\beta_y^*} \left(\frac{R_L}{R_y} \right)$$

Classical electron radius

Beam size ratio

Geometrical repipeion factors due to crossing angle and hour-glass effect

Luminosity:

$$0.17 \times 10^{35} \text{ cm}^{-2} \text{s}^{-1} \text{ (KEKB)}$$

$$8 \times 10^{35}$$
 cm⁻²s⁻¹ (SuperKEKB)

Vertical β at the IP:

6.5/5.9 mm (KEKB)

→ 3.0/3.0 mm (SuperKEKB)


Costs & Effects Preliminary


	ltem	Object Oku-ye		Luminosity	
	New beam pipes	Enable high current Reduce e-cloud	178 (incl. BPM, magnets, etc.)	x1.5	
	New IR	Small \(\beta^*\)	31	x2	
	e+ Damping Ring	Allow injection with small increase e+ capture	40 incl. linac upgrade	if not, x0.75	
	More RF and cooling systems	High current	179 (incl. facilities)	x3	
Crab Cavities		Higher beam-beam param.	15	x2 - x4	


Items are interrelated.

KEKB has 22 mrad horizontal crossing angle at the IP:

- Easier beam separation
- •Simpler design around the IP.
- •Less number of components.
- •Less synchrotron radiation.
- •Less luminosity-dependent background.
- •Space for compensation solenoid, etc.








Crab Crossing @ KEKB

•Crab Crossing can boost the beam-beam parameter higher than 0.15!

K. Ohmi




Head-on (crab)

(Strong-strong simulation)


Crossing angle 22 mrad

•Crab cavities were successfully produced and beam study has started in Feb. 2007.



More gain than geometrical overlap is expected:


Head-on + hor. half integer tune
≈ 10 + synchrotron motion



head-on: beam distribution is symmetric in x.

The beam-beam force becomes nearly independent on x at horizontal half integer and with head-on collision (Ohmi & Perevedentsev)

Single Crab Cavity Scheme



* 1 crab cavity per ring.

- Beam tilts all around the ring.
- *z-dependent horizontal closed orbit.
- otilt at the IP:

$$\frac{\theta_x}{2} = \frac{\sqrt{\beta_x^C \beta_x^*} \cos(\psi_x^C - \mu_x/2)}{2\sin(\mu_x/2)} \frac{V_C \omega_{\text{rf}}}{Ec}$$


Table 1: Typical parameters for the crab crossing.

Ring	LER	HER	
θ_x	22		mrad
$\parallel eta_x^*$	80	80	\overline{cm}
	73	162	\mathbf{m}
$\parallel \mu_x/2\pi$	0.505	0.511	
$\mu_x/2\pi$ $\psi_x^C/2\pi$	~ 0.25	~ 0.25	
V_C	0.95	1.45	V
$\omega_{ m rf}/2\pi$	509		MHz

- * saves the cost of the cavity and cryogenics.
- * avoids synchrotron radiation hitting the cavity.

Crab Cavity & Coaxial Coupler in Cryomodule


K. Hosoyama et al



Phase stability

- * Spectrum of pick up signal is consistent with phase detector data.
- * Phase fluctuation faster than 1 kHz is less than ±0.01°, and slow fluctuation from ten to several hundreds of hertz is about ±0.1°.
- * They are much less than the allowed phase error obtained from the beam-beam simulations for the crabbing beams in KEKB.

According to b-b simulation by Ohmi-san, allowed phase error for N-turn correlation is 0.1×√N (degree).



CENTER 503.83575MHz


CENTER 503.83575MHz

VBW 10Hz

VBW 10Hz

SPAN 10.00kHz


SWP.3.78sec



Span 200 kHz Sideband peaks at 32kHz and 64kHz.

Span 10 kHz

Span 500 Hz Sideband peaks at 32, 37, 46, 50, 100 Hz.



Phase detector signal. Beam current was 385mA (HER) and 600 mA (LER).

Spectrum around the crabbing mode measured at a pick up port of the LER crab cavity. Beam current was between 450 and 600 mA.



Finally two crab cavity was installed in KEKB, one for each ring in January 2007.




HER (e-, 8 GeV)





LER (e+, 3.5 GeV)

Beams has indeed tilted!


- Observation with Streak Cameras (H. Ikeda et al, FRPMN035)







Specific Luminosity




- * A number of measurements indicate effective head-on collision.
- * The vertical tune shift became higher than 0.088. Before crab, it was 0.055.
- The specific luminosity / bunch was improved more than the geometrical gain.
- * Need more time to achieve the goal (X2 specific luminosity).

Why the specific luminosity drops faster than expected?

Speculations:

- * The single beam vertical emittance may have to be sufficiently small
- * Lifetime may be limited by the dynamic- β and dynamic emittance caused by bea-beam.
- * Electron Cloud in the LER: Luminosity becomes better for longer bunch spacing.
- * The SPOOABS nature in the optimum condition of the collision: Too many parameters.
- * Synchrotron-betatron resonance near 1/2 integer.
- * .. and more ..


Vertical emittance small enough?



K. Ohmi


According to the simulation, the vertical singlebeam emittance must be less than 1% to achieve the high luminosity(above).


 Recent calibration of the size monitor with "iSize" bump orbit shows the emittance ratio was 1.4%/1.2% for LER/HER (right).



N. lida et al, TUPAN042

The legacy coupling & dispersion correction may not be sufficient to recover the luminosity







new/old orbit

- **skew quads** closer to the model.
- flatten vertical orbit in the arcs.
- Include BPM rolls as variables of the xy coupling correction.

old/new skew quads



LER dynamic-\beta and emittance




LER	
$v_{\mathbf{x}}$	45.506
∨ _v	43.57
β _x [m]	.9
β _ν [m]	.0059
ξ _s max	.09
ξ _ψ max	.1

The focusing force of the beam-beam interaction not only squeezes the beam at the interaction point, but increases the emittance drastically.


Y. Funakoshi

Deformation of βfunction all around
the ring due to
beam-beam effect
("dynamic beta")





Y. Funakoshi

The lifetime may be limited by the dynamic beta effect.




Are we already close to simulation?





Specific Luminosity becomes better for longer bucket spacing. Due to e-cloud?



Too many tuning knobs?

Table 3: Tuning knobs for the crab crossing and their observables. Many depend only on the beam size σ_y at the synchrotron radiation monitor (SRM), besides the luminosity \mathcal{L} .


Knob	Observable	frequency: every	
Relative beam offset IP	Beam-beam kick measured by BPMs around the IP	1 sec	2
Relative beam angle IP	BPMs around the IP	1 sec	2
Global closed orbit	All \sim 450 BPMs	15 sec	-
Beam offset at crab cavities[11]	BPMs around the crab cavity	1 sec	2
Betatron tunes	tunes of non-colliding pilot bunches	$\sim 20~{\rm sec}$	4
Relative rf phase	center of gravity of the vertex	10 min.	1
Global couplig, dispersion, beta-beat	orbit response to kicks & rf frequency	\sim 14 days	
LER to HER crab voltage ratio	response in the hor. beam-beam kick. vs. crab rf phase	\sim 7 days	1
Rf phase of crab cavity	hor. kick vs. crab voltage response	\sim 7 days	2
Vertical waist position	${\cal L}$ and σ_y at the SRM	\sim 1 day	2
Local x-y couplings and dispersions at IP	${\cal L}$ and σ_y at the SRM	\sim 1 day each	16
Sextupole settings	${\cal L}$ and lifetime	\sim 3 days	106
X-y coupling parameter at the crab cavities	${\cal L}$ and σ_y at the SRM	\sim 3 days	4
Crab kick voltage	${\cal L}$ and σ_y at the SRM	\sim 7 days	2

- Many knobs are determined by scans only on the luminosity, beam sizes, and the lifetime.
- Scan is slow, each takes about 30 minutes.
- Question in the multi-dimensional nonlinear optimization.

sharply-peaked-optimum-on-a-broad- shoulder (SPOOABS)


An example: the Horizontal Offset and the crossing angle at the IP

Luminosity beam-beam kick





- Luminosity degrades by ä small error in any one of the collision parameters. The horizontal offset of two beams and the crossing angle at the IP are such an example.
- Horizontal offset must be much less than 25 μm , and the crossing angle less than 1.5 mrad to see the effect of crab crossing.
- There are more than 20 of such parameters. If one of them is largely off, the optima of other parameters cannot be found.

Synchrotron-betatron resonance




- The horizontal tune is set nearby the half integer resonace and its synchrotron sidebands.
- At the resonance, the single beam beam sizes blowup(left).
- This effect can be calculated by "anomalous emittance" effect.
- The blowup depends on the sextupole setting (below).





Finding better sextupole setting: "bungee jump"



Three factors to determine the luminosity:

Stored current:

 $1.7 / 1.4 A (e^{+}/e^{-}KEKB)$

→ **9.4** /**4.1** A (SuperKEKB)

Beam-beam parameter:

0.059 (KEKB)

→ >0.24 (SuperKEKB)

Lorentz factor

$$L = \frac{\gamma_{\pm}}{2er_e} \left(1 + \frac{\sigma_y^*}{\sigma_x^*} \right) \frac{I_{\pm} \xi_{\pm y}}{\beta_y^*} \left(\frac{R_L}{R_y} \right)$$

Classical electron radius

Beam size ratio

Geometrical repipeion factors due to crossing angle and hour-glass effect

Luminosity:

$$0.17 \times 10^{35} \text{ cm}^{-2} \text{s}^{-1} \text{ (KEKB)}$$


$$8 \times 10^{35}$$
 cm⁻²s⁻¹ (SuperKEKB)

Vertical β at the IP:

6.5/5.9 mm (KEKB)


→ 3.0/3.0 mm (SuperKEKB)

Vacuum components: Bellows chamber with comb type RF-shield





- Low impedance
- No sliding contact on the surface facing the beam






Comb-type bellows were installed in the LER (2004).

Beam pipe with antechamber Manufacturing

- Cold drawn copper pipe, and welded by EB.
- MO-type flange (stain-less steel).
- BPM electrode was connected by ICF flange.
- No mapping before installation;
 Gain mapping will be done by BBA

Straight pipe






Y. Suetsugu

BPM

Beam pipe with antechamber TiN coating

- TiN was coated in KEK (K. Shibata et al.)
- Coating system available for ~4 m pipe was set up.
- Thickness is ~200 nm, which is determined from adhesiveness of film and δ_{max} (~0.84).



Gas inlet

Solenoid

Pipe






Pumping system

Y. Suetsugu

Movable Mask Ver.6 Concept

Proposal : Metal head supported by dielectric material



 Little interference with beam **Small** Loss factor 10 Ver.4 oss factor [V/pC] Ver.6 0.01

6


10

0.001


Movable Mask Ver.6 The first test model (Ver. 6.0)

- In 2006, Ver.6.0 was manufactured.
- Head: Al₂O₃ Coated with copper
- Support: Al₂O₃ (Ti coating at one side)
 - Head and support was shaped as a unit.
- HOM absorber: SiC (Inside of chamber)
- Installed into LER for proof of concept.

Inside view of mask chamber



Mask head and support of Ver.6.0



The ARES Cavity

Accelerator Resonatly-coupled Energy Storage

T. Kageyama, et al


Passive stabilization with huge stored energy.

Eliminate unnecessary modes by coupling of 3 cavities.


Higher order mode dampers and absorbers.


No need for longitudinal bunch-by-bunch feedback.

No transverse instability arises from the cavities.



High power RF R&P





- * Upgrade of ARES with higher energy storage ratio. (left)
- * High power rf input couplers.
- * SiC dummy load with higher power capability (right).


Superconducting Cavity



HER IR

$$\beta_x^* = 4.78$$
cm, $\epsilon_x = 98.7$ nm ($\beta_{x=0}^* = 40$ cm, $\epsilon_{x0} = 12$ nm)(red)

$$\beta_{x}^{*}$$
 = 4.45cm, ϵ_{x} = 217nm ($\beta_{x=0}^{*}$ = 20cm, ϵ_{x0} = 24nm)(blue)




The dynamic beta and dynamic emittance effects enlarge beam sizes at IR magnets drastically.

This physical aperture issue seems serious.

IR design work is still going on to overcome this issue.

Local chromaticity correction



Effects of local correction

- widen dynamic aperture
- weaken synchro-betatron resonance

KEKB:

local correction only in LER KEKB upgrade:

local correction also in downstream of HER





Construction of QCS R&D Magnet

N. Ohuchi

(2-4) 12 Cured Coils and curing 6 layer coils all at once








- (1) 12 cured double pan-cake coils.
- Curing process of 6 layer coils. This process is necessary for improving the field quality in the magnet straight section (magnet body).



Frequency (kHz)

A prototype of the new bunch-by-bunch feedback system (G-board / Gproto) was tested at KEKB and ATF. The results were quite successful.




- •Even in single-bunch mode, we observed a strong longitudinal instability at the ATF.
- •In multi-bunch mode, we observed a strong CBI.
- •Successfully damped the longitudinal CBI with the BxB feedback system using Gproto down to 1/10.
- Successfully analyzed strongest coupled-bunch mode. (218+n*357 MHz)
- •For practical use, it will be necessary to build and install a good feedback kicker.

M. Tobiyama

- C-band linac: completed a single section in the linac with 4 structures.
- Performance was satisfactory with the beam.

T. Kamitani, et al



C-Band Klystrons

-		S-band	C-band							
	Parameters	KEKB	1-st prototype	2m-structure	Unit					
	total length	2.072	1.082	2.0	m					
	number of regular cells	54	54	108						
	regular cell length (d)	35.0	17.5	17.5	mm					
	disk thickness (t)	5.0	2.5	2.5	mm					
	disk iris diameter (2a)	24.95 - 20.90	12.48 - 10.45	14.03 - 10.54	mm					
	cavity diameter (2b)	83.0 - 82.0	41.5 - 41.0	42.0 - 41.0	mm					
	group velocity (v_g/c)	1.4	1.9 - 1.0	2.8 - 1.0	%					
	shunt impedance	57	75 - 85	67 - 85	$M\Omega/m$					
	Q factor	13700	9690	9700						
	RF power in cells	30 - 15	34 - 15	<u> 59 - 15</u>						
	Field gradient	21	41.2 - 39.0	42.5 - 38.1	00					
	Filling time	462	234	376	30					

Table 11.3: Accelerating section characteristics

0.434

0.696

0.302

Attenuation constant





Figure 11.7: C-band 1m-long accelerating section (1-st prototy

Prototype C-band structure installed and tested at linac using actual beam (2003). Measured field gradient of 41 MV at 43 MW agrees with expectation.

Energy Gain by C-band unit



T. Kamitani, et al

Damping Ring


- * Positron emittance needs to be damped, to pass reduced aperture of C-Band section and to meet IR dynamic aperture restrictions.
 - * Electron DR may be considered later to reduce injection backgrounds in physics detector, but for now only positron DR considered.
- * Damping ring located downstream of positron target, before C-Band accelerating section.

M. Kikuchi



Cost Estimation (in Oku-yen = 1.0 M\$)


	Old estimation Full Spec SuperKEKB	Construction (for 3 years)	Upgrade during operation	Total
Vacuum	116.86	139.36	0	139.36
RF	115.873	16.45	84.25	100.7
Infrastructure	84.3	3	75.2	78.2
Magnet	16.7008	31.9	0	31.9
Crab	17	5	10	15
Beam monitor	174684	17.7	4.5	22.2
Injector	58	10	53.7	63.7
Pamping Ring (other than RF, monitor)	16.8	0	21.26	21.26
Control	9.4	2	7.4	9.4
IR	8	14.7	0	14.7
Beam transport	2.5	2.5	0	2.5
Total	462.9022	242.61	256.31	498.92



Compatibility with Italian option

LER arc cell

Preliminary



 $\varepsilon_x = 6.8 \text{ nm}$

- $\varepsilon_{x} = 2.2 \text{ nm}$
- The arc cell lattice of the KEKB LER (left) can be modified to the low-emittance version (right), by weakening the magnetic field of the dipoles.
- No need for changing other components, beam pipes, geometry.
- The interaction region must be rebuilt.
- The HER's emittance is not reduced, but unequal emittance may be OK.